


Hittebestendige polyester maskeertape +204°C

Hitzebeständiges Polyesterfilm Abdeckband +204°C

Heat resistant polyester film adhesive masking tape +204°C

General information

- Heat resistant polyester film adhesive masking tape is available in widths from 5mm to 500mm inclusive – larger widths on request.
- Green polyester film 60µm thick, thicker possible on request
- Silicone adhesive, pressure sensitive
- Applicable manually or with a machine thanks to its consistent unwinding force.
- Easy and clean removal without residue remains
- Its flexibility makes it conformable and particularly suitable for non-leak seals
- Doesn't shrink
- Temperature resistant up to +204°C during maximal 30 minutes
- Good resistance against chemicals
- The tape enables sharp colour edges and doesn't affect coating adhesion
- This green heat resistant polyester masking tape is suitable for masking surfaces during high temperature operations like wet coating, powdercoating, E-coating, galvanic surface treatment, anodizing and soldering printed circuits



Specifications

Colour	green
Tape thickness	
Film	0.038 mm
Total	0.070 mm
Backing	Polyester
Adhesive type	Silicone
Adhesion to steel (N/25mm)	7-8
Tensile strength (N/25mm)	≥120
Elongation at Break (%)	≥170
Breakdown strength (N/25mm)	≥150
Storage condition	20°C / 65%R.H / 68 °F / 65%R.H

Voltage resistance	4 KV		
Maximum temperature resistance	204°C	/	399.2 °F
Length per roll	66 m	/	72 yd
Width	5-500mm	/	0.2 – 19.68 inch